

Changes allowed yet not required	Changes not Allowed and must remain in OEM form	Must Have	Questionable
Handle Bars	engines have to use brand model OEM parts	Nerf Bars	after market steering stem (Height and clamp)
Hand Guards	Intake	Killswitch	Wheel size
Clutch Lever	Head pipe		Tire Size
Grips	Frame		Cherry bomb (suz)
Bumper	Ti Bolts		Flashing the ECU
Grab Bar	Chassi- Frame, A-arms, swing arm, linkage,		light weight battery
Wheels- Maybe Stock dimensions	Air Box		breather box
Tires- Maybe Stock Dimensions	All Hubs (wheel and sprocket)		
Exhaust- Slip on only	ECU		
Steering Stabilizer	Clutch arm		
Modify Stock shocks internals body and shaft have to remain OEM - Springs allowed	seat foam or pan		
Chains	steering stem stock flag points		
Sprockets	Ceramic Bearings		
Remove emissions pieces	No after market programmers		
remove oem safety reflectors	break pedal extenders		
Timing plugs			
replacement Cables			
Replacement Bushings			
Change/ Modified Plastics			
Seat Covers			
Filter with oem mounting			
Rotors			
Break Pads			
Remove Air Box Lid			
wiring hardness			
Add capasitor			
remove head light and break light			
remove parking brake			
powder coat / paint			
chain guides			
Break Lines			
Non oem replacement bearings			
Frame guesset for strength only			
Subframe support rails			
Clutch fibers			
Handle bar risers			
skid plates			
Bolt on chain guides			
Move ECU			
sauter fuel pump connection			